

**LYNX**

# 49 RANGER PRO

## 2021



### ROTAX® ENGINE

	600R E-TEC	900 ACE
<b>Engine details</b>	Liquid-cooled, 3-D R.A.V.E.™	Liquid-cooled, four-stroke D.O.H.C., dry sump
<b>Cylinders</b>	2	3
<b>Displacement</b>	599.4 cc	899.0 cc
<b>Bore</b>	72,3 mm	74 mm
<b>Stroke</b>	73 mm	69.7 mm
<b>Maximum engine speed</b>	8100 RPM	7250 RPM
<b>Carburation</b>	Electronic Direct Injection	EFI
<b>Recommended fuel type</b>	Unleaded	Unleaded
<b>Minimum octane</b>	95	95
<b>Fuel tank</b>	37 liters	37 liters
<b>Oil tank capacity (2-stroke)</b>	3.4 liters	

### POWERTRAIN

<b>Drive clutch type</b>	pDrive with clickers (600R E-TEC) pDrive (900 ACE)
<b>Driven clutch type</b>	QRS
<b>Brake system</b>	Hydraulic brake with braided steel brake line, plastic master cylinder

### FEATURES

<b>Frame</b>	Radien-X
<b>Skis</b>	Blade DS+
<b>Seating</b>	2-up light
<b>Handlebar</b>	U-type steel with hooks, low grab handle
<b>Riser block height</b>	140 mm
<b>Starter</b>	Electric (900 ACE) Electric and manual (600R E-TEC)
<b>Reverse</b>	RER (600R E-TEC) Mechanical (900 ACE)

### COLOUR

Full Moon Silver/Orange/Black

### DIMENSIONS

<b>Vehicle overall length*</b>	3530 mm
<b>Vehicle overall width</b>	1120 mm (600R E-TEC) 1200 mm (900 ACE)
<b>Vehicle overall height</b>	1490 mm
<b>Ski stance</b>	921 mm (600R E-TEC) 996 mm (900 ACE)
<b>Track nominal width</b>	406 mm
<b>Track nominal length</b>	4141 mm
<b>Track profile height</b>	59 mm Powder Max FlexEdge

### SUSPENSION

<b>Front suspension</b>	LFS with bended lower A-Arms
<b>Front shock</b>	HPG 36
<b>Rear suspension</b>	EasyRide
<b>Center shock</b>	HPG 36
<b>Rear shock</b>	HPG 36

<b>Heated throttle lever</b>	Standard
<b>Heated grips</b>	Standard
<b>Gauge</b>	7.2-in. wide digital display
<b>Mirrors</b>	
<b>Windshield</b>	Extra high with side deflectors
<b>Hitch</b>	Standard
<b>Visor Plug front / rear</b>	Front
<b>12V power outlet</b>	Yes, in front compartment

\* Vehicle overall length without snowflap.

©2020 Bombardier Recreational Products Inc., (BRP). All rights reserved. ™, \* and the BRP logo are trademarks of BRP or its affiliates. †All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.

