



ROTAX® ENGINE

900 ACE

| | |
|------------------------------|--|
| Engine details | Liquid-cooled, four-stroke D.O.H.C., dry sump |
| Cylinders | 3 |
| Displacement | 899.0 cc |
| Bore | 74 mm |
| Stroke | 69.7 mm |
| Maximum engine speed | 7250 RPM |
| Carburation | EFI |
| Recommended fuel type | Unleaded |
| Minimum octane | 95 |
| Fuel tank | 42 liters |

POWERTRAIN

| | |
|---------------------------|---|
| Drive clutch type | pDrive |
| Driven clutch type | QRS |
| Brake system | Hydraulic brake with braided steel brake line, plastic master cylinder |

FEATURES

| | |
|---------------------------|---|
| Frame | Radien-X |
| Skis | Blade DS+ |
| Seating | Modular, 1-up heated |
| Handlebar | U-type steel with hooks, low grab handle |
| Riser block height | 140 mm |
| Starter | Electric |
| Reverse | Electromechanical |

COLOUR

White/Orange/Black

DIMENSIONS

| | |
|--------------------------------|---------|
| Vehicle overall length* | 3240 mm |
| Vehicle overall width | 1200 mm |
| Vehicle overall height | 1490 mm |
| Ski stance | 996 mm |
| Track nominal width | 600 mm |
| Track nominal length | 3968 mm |
| Track profile height | 32 mm |

SUSPENSION

| | |
|-------------------------|---------------------------------|
| Front suspension | LFS with bended lower A-Arms |
| Front shock | HPG 36 |
| Rear suspension | EasyRide with adjustment |
| Center shock | HPG 36 |
| Rear shock | HPG 36 |

| | |
|--------------------------------|---------------------------------|
| Heated throttle lever | Standard |
| Heated grips | Standard |
| Gauge | 4.5-in. digital display |
| Mirrors | Standard |
| Windshield | Extra high with side deflectors |
| Hitch | Standard |
| Visor Plug front / rear | Front |
| 12V power outlet | Front |

* Vehicle overall length without snowflap.