

**LYNX**

# BOONDOCKER RE 3700

**2021**

## ROTAX® ENGINE

### 850 E-TEC

<b>Engine details</b>	Liquid-cooled, 3-D R.A.V.E.™
<b>Cylinders</b>	2
<b>Displacement</b>	849 cc
<b>Bore</b>	82 mm
<b>Stroke</b>	80.4 mm
<b>Maximum engine speed</b>	7900 RPM
<b>Carburation</b>	Electronic Direct Injection with additional booster injectors
<b>Recommended fuel type</b>	Unleaded
<b>Minimum octane</b>	95
<b>Fuel tank</b>	37 liters
<b>Oil tank capacity (2-stroke)</b>	3.4 liters

## POWERTRAIN

<b>Drive clutch type</b>	pDrive with clickers
<b>Driven clutch type</b>	QRS
<b>Brake system</b>	Hydraulic brake with braided steel brake line, plastic master cylinder

## FEATURES

<b>Frame</b>	Radien
<b>Skis</b>	Blade DS+
<b>Seating</b>	BoonDocker, 1-up
<b>Handlebar</b>	U-type aluminium with hooks, low grab handle
<b>Riser block height</b>	140 mm
<b>Starter</b>	Manual SHOT (spring only)
<b>Reverse</b>	RER

## COLOUR

Orange

## DIMENSIONS

<b>Vehicle overall length*</b>	3130 mm
<b>Vehicle overall width</b>	1200 mm
<b>Vehicle overall height</b>	1290 mm
<b>Ski stance</b>	996 mm
<b>Track nominal width</b>	406 mm
<b>Track nominal length</b>	3705 mm
<b>Track profile height</b>	64 mm PowderMax FlexEdge

## SUSPENSION

<b>Front suspension</b>	LFS
<b>Front shock</b>	KYB 36 CR Kashima
<b>Rear suspension</b>	PPS <sup>2</sup> -3700
<b>Center shock</b>	KYB 46 HLCR Kashima
<b>Rear shock</b>	KYB 46 HLCR Kashima

<b>Heated throttle lever</b>	Standard
<b>Heated grips</b>	Standard
<b>Gauge</b>	4.5-in. digital display
<b>Mirrors</b>	
<b>Windshield</b>	
<b>Hitch</b>	
<b>Visor Plug front / rear</b>	
<b>12V power outlet</b>	Yes, in front compartment

\* Vehicle overall length without snowflap.

©2020 Bombardier Recreational Products Inc., (BRP). All rights reserved. ™, \* and the BRP logo are trademarks of BRP or its affiliates. †All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.



**LYNX**

# BOONDOCKER RE 3900

**2021****ROTAX® ENGINE****850 E-TEC**

<b>Engine details</b>	Liquid-cooled, 3-D R.A.V.E.™
<b>Cylinders</b>	2
<b>Displacement</b>	849 cc
<b>Bore</b>	82 mm
<b>Stroke</b>	80.4 mm
<b>Maximum engine speed</b>	7900 RPM
<b>Carburation</b>	Electronic Direct Injection with additional booster injectors
<b>Recommended fuel type</b>	Unleaded
<b>Minimum octane</b>	95
<b>Fuel tank</b>	37 liters
<b>Oil tank capacity (2-stroke)</b>	3.4 liters

**POWERTRAIN**

<b>Drive clutch type</b>	pDrive with clickers
<b>Driven clutch type</b>	QRS
<b>Brake system</b>	Hydraulic brake with braided steel brake line, plastic master cylinder

**FEATURES**

<b>Frame</b>	Radien
<b>Skis</b>	Blade DS+
<b>Seating</b>	BoonDocker, 1-up
<b>Handlebar</b>	U-type aluminium with hooks, low grab handle
<b>Riser block height</b>	140 mm
<b>Starter</b>	Manual SHOT (spring only)
<b>Reverse</b>	RER

**COLOUR**

Orange

**DIMENSIONS**

<b>Vehicle overall length*</b>	3240 mm
<b>Vehicle overall width</b>	1200 mm
<b>Vehicle overall height</b>	1300 mm
<b>Ski stance</b>	996 mm
<b>Track nominal width</b>	400 mm
<b>Track nominal length</b>	3912 mm
<b>Track profile height</b>	64 mm PowderMax Light FlexEdge

**SUSPENSION**

<b>Front suspension</b>	LFS
<b>Front shock</b>	KYB 36 CR Kashima
<b>Rear suspension</b>	PPS <sup>2</sup> -3900
<b>Center shock</b>	KYB 46 HLCR Kashima
<b>Rear shock</b>	KYB 46 HLCR Kashima

<b>Heated throttle lever</b>	Standard
<b>Heated grips</b>	Standard
<b>Gauge</b>	4.5-in. digital display
<b>Mirrors</b>	
<b>Windshield</b>	
<b>Hitch</b>	
<b>Visor Plug front / rear</b>	
<b>12V power outlet</b>	Yes, in front compartment

\* Vehicle overall length without snowflap.

©2020 Bombardier Recreational Products Inc., (BRP). All rights reserved. ™, ® and the BRP logo are trademarks of BRP or its affiliates. All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.

