§MAVERICK™ X™rs TURBO RR

HIGHI IGHTS

PLATFORM FEATURES

185 cm wide

DEFIANT

- 259 cm wheelbase
- 40.0
- 40.6 cm of ground clearance
 High torque Dynamic Power Steering (DPS™)
- Up to 61 cm suspension travel

Trademark Can-Am DNA with

next generation design

· Ergo-Lok cockpit with four-

Low seating position

way adjustable seats

SPECIFIC TO X rs PACKAGE

- 195 hp Turbo RR engine
- Smart-Lok[™]* front differential
- FOX[†] 3.0 PODIUM[†] RC2 rear shocks with bypass
- 14-in. aluminum beadlock wheels
- 30-in. Maxxis[†] Bighorn 2.0[†] tires
- 4-point harness with shoulder pads
- HMWPE heavy-duty full skid plate
- X-package graphics/seats
- 7.6-in. digital display with keypad
- Painted color options

POWERFUL

- 195 hp turbocharged and intercooled Rotax® ACE engine
- Advanced airflow dynamics
- QRS-X transmission

PRECISE

- TTX suspension with industry leading travel
- Ultra efficient and lightweight chassis
- Sharpest handling features





Hyper Silver, Intense Blue & Manta Green / TURBO RR

ENGINE	TURBO RR	
Туре	195 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and high-perfomance air filter	
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
Transmission	Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R/P	
Drive Train	Lockable front differential with exclusive Smart-Lok* technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL	
	*Smart Lak was developed in conjunction with TEAM Industries a market leader in the drive train industry	

High torque Iri-Mode Dynamic Power Steering (DPS)		
Double A-arm with sway bar / 55.9 cm travel / Trophy truck inspired arms		
FOX 2.5 PODIUM RC2 Piggyback with bypass, dual speed compression and rebound adjustments		
4-link Torsional Trailing-arm X (TTX) with sway bar 61 cm travel		

	of cill flavel		
Rear Shocks	FOX 3.0 PODIUM RC2 remote reservoir with bypass, dual speed compression and rebound adjustments		
BRAKES			
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers		
Rear Dual 248 mm ventilated disc brakes with hydraulic twin-piston of			

TIRES / WHEE	LS
Front Tires	Maxxis Bighorn 2.0 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 30 x 11 x 14 in. (76.2 x 27.9 x 35.6 cm)
Wheels	14-in. (35.6 cm)

DIMENSIONS /	CAPACITIES		
LxWxH	335.3 x 184.7 x 174 cm		
Wheelbase	259.1 cm		
Ground Clearance	40.6 cm		
Estimated Dry Weight	738 kg		
Chassis / Cage	Dual-phase 980 steel		
Rack Capacity	91 kg with LinQ™ quick-attach		
Storage Capacity	Total: 9.4 L Glove box: 6.2 L Center console: 2.8 L Cup holders: 0.4 L		
Fuel Capacity	40 L		

FEATURES			
Gauge	7.6 in. (19.3 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, SPORT / ECO™ modes, seat belt, diagnostics, clock	Protection	Integrated front bumper , quarter-doors, full roof, 4-point harness with shoulder pads, HMWPE heavy- duty full skid plate, rear tow hook
Instrumentation	Lighter type DC outlet in central console	Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	N/A	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/ Stop button

WARRANTY

Factory 2 years

©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. 'All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed.

