©OUTLANDER™ 6x6 PRO+ 450 T

HIGHLIGHTS

- Rotax® engine
- Intelligent Throttle Control (iTC™)
- Continuously Variable Transmission (CVT) with extra low L-gear
- Tri-Mode Dynamic Power Steering (DPS)
- 1,361 kg (3,000 lbs) WARN winch with roller fairlead
- 26-in. Carlisle† ACT HD 6-ply tires
- 12-in. cast-aluminum wheels
- Double Torsional Trailing arm Independent (TTI2) rear suspension
- Double A-arm front suspension

- Relocated air intakes
- · Reinforced seat skin
- Digitally Encoded Security System (D.E.S.S.™)
- 10.9 L water-resistant rear compartment
- 159 kg capacity rear bed with cargo extenders
- Quick release rear sway bar
- Heated hand grips



Green

ENGINES	450
Туре	38 hp, Rotax 427 cc single cylinder, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC TM) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 4WD / 6WD with Visco-Lok QE† auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed category	Up to 60 km/h

SUSPENSIONS	
Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Oil
Rear Suspension	Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar with 22.4 cm travel
Rear Shocks	0il

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHE	ELS
Front Tires	Carlisle ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS /	CAPACITIES
LxWxH	279 x 118.8 x 124 cm
Wheelbase	208 cm
Ground Clearance	26.7 cm
Seat Height	85.8 cm
Dry Weight	443 kg
Rack Capacity	Front: 54 kg Rear: 159 kg
Storage Capacity	Rear: 70 L
Towing Capacity	907 kg trailer with brakes and 465 kg trailer without brakes
Fuel Capacity	20.5 L

FEATURES			
Gauge	Multifunction digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	70 W from dual 35-W front light / brake light
		Seat	Reinforced seat skin
Winch	1361 kg (3,000 lbs) WARN winch with roller fairlead	Anti-theft System	Digitally Encoded Security System (D.E.S.S.)
T-category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn	Protection	Heated hand grips

WARRANTY		
Factory	2 years	



