## **©OUTLANDER™ MAX XT™ 650**

## **HIGHLIGHTS**

- Rotax® V-twin engine
- Intelligent Throttle Control (iTC™) with riding modes
- Arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 1,361 kg WARN<sup>†</sup> winch with roller fairlead
- Heavy-duty front and rear bumpers
- 14-in. cast-aluminum wheels

- 26-in. ITP<sup>†</sup> Terracross radial tires
- Painted plastics for premium look
- Handlebar wind deflectors
- Convertible Rack System (CRS) with LinQ™ system
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips
- Raised floorboards
- 21.4 L water-resistant rear compartment



Mossy Oak† Break-Up Country Camo†

ENGINES	650
Туре	59 hp, Rotax 649.6 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok <sup>‡</sup> QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar 23.3 cm travel
Front Shocks	0il
Rear Suspension	Torsional Trailing arm Independent (TTI) 25.1 cm travel
Rear Shocks	0il

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES / WHEELS	
Front Tires	ITP Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm)
Rear Tires	ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)
Wheels	14-in. cast-aluminum

DIMENSIONS / CAPACITIES				
LxWxH	239 x 122 x 135 cm			
Wheelbase	149.9 cm			
Ground Clearance	27.9 cm			
Seat Height	87.7 cm			
Engine / Dry Weight*	375 kg			
Rack Capacity	Front: 45 kg Rear: 90 kg			
Storage Capacity	Rear: 21.4 L			
Towing Capacity	750 kg			
Fuel Capacity	20.5 L			

<b>FEATURES</b>			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Convertible Rack System (CRS)
Winch	1,361 kg WARN winch with roller fairlead	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Heavy-duty front & rear bumpers, handlebar wind deflectors, mudguards		

WARRANTY	
Factory	2 years

