RENEGADE X° xc 650 T

HIGHLIGHTS

- Rotax® V-twin engine
- Intelligent Throttle Control (iTC[™]) with riding modes
- Anti-Lock Brake System (ABS)
- Front and rear FOX[†] PODIUM[†] 1.5 RC2
- front sway bar
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 12-in. cast-aluminum beadlock wheels
- 25-in. ITP Holeshot† ATR tires

- Front & central skid plate
- Aluminum taper-profile handlebar with wind deflectors and square pad
- Torsional Trailing arm Independent (TTI) rear suspension
- Multifunction digital gauge
- Arched double A-arm front suspension with X-package coloration, graphics and seat



Black, Grey & Sunburst Yellow

ENGINES	650
Туре	59 hp, Rotax 649.6 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Brake Traction Control (BTC)
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed category	More than 60 km/h

SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar 23.3 cm travel
Front Shocks	FOX† PODIUM† 1.5 RC2
Rear Suspension	Torsional Trailing arm Independent (TTI) 25.1 cm travel
Rear Shocks	FOX† PODIUM† 1.5 RC2

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brakes with hydraulic twin-piston calipers
ABS	Standard

TIRES / WHEELS	
Front Tires	ITP Holeshot ATR 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	ITP Holeshot ATR 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum beadlocks

DIMENSIONS /	CAPACITIES
LxWxH	218.4 x 122 x 124 cm
Wheelbase	129.5 cm
Ground Clearance	26.7 cm
Seat Height	87.7 cm
Dry Weight*	303 kg
Rack Capacity	Rear: 16 kg
Storage Capacity	N/A
Towing Capacity	660 kg trailer with brakes and 335 kg trailer without brakes
Fuel Capacity	20.5 L

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	240 W from 4 fender mounted projector beam headlamps (60 W) with tail light / brake light
		Seat	Standard
Winch	Prewired for available winch	Anti-theft System	Digitally Encoded Security System (D.E.S.S.)
T-category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn	Protection	Front bumper, aluminum taper-profile handlebar with wind deflectors and square pad, front & central skid plate, mudguards

WARRANTY	
Factory	2 years

