STRAXTER PRO HD10 T

HIGHLIGHTS

TOUGH

- Heavy-duty Rotax® engine
- Smooth, durable and responsive transmission
- True Can-Am DNA with a strong

CAPABLE

- Work or ride with confidence
- Meaningful and versatile functionality
- Easy handling and capabilities

CLEVER

- Advanced comfort and intuitive
- cockpit with optimized visibility Multifunction cargo box with
- sturdy tailgate and smart storage
- 1-year maintenance free and easy access to key maintenance components



- Dynamic Power Steering (DPS™) Lockable rear differential and Visco-Lok[†] QE autolocking front differential
- 14-in. cast-aluminum wheels with 27-in. Maxxis Coronado tires
- VERSA-PRO bench seat with reinforced seat skin
- HMWPE Full skid plate
- 2,041 kg winch with roller fairlead
- Horn with turning signal
- Flashers and position lamps
- Mirrors
- Brake holding mechanism



Hyper Silver

ENGINE	HD10
Туре	82 hp, Rotax 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PRO-TORQ transmission with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Lockable rear differential and Visco-Lok† QE auto-locking front differential
Driving Assistance	Electronic Hill Descent Control ECO™ / ECO Off / Work modes
Power Steering	Dynamic Power Steering (DPS)
Speed category	Up to 60 km/h

SUSPENSIONS	
Front Suspension	Arched double A-arm 27.9 cm travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	Arched TTA with external sway bar 27.9 cm travel
Rear Shocks	Twin tube gas charged shocks

BRAKES	
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm ventilated disc brakes with hydraulic single-piston calipers

TIRES / WHEELS	8
Front Tires	Maxxis Coronado 27 x 9 x 14 in. (68.6 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Coronado 27 x 11 x 14 in. (68.6 x 27.9 x 35.6 cm)
Wheels	14 in. cast-aluminum

DIMENSIONS / C	CAPACITIES		
LxWxH	305 x 162.5 x 203.2 cm		
Wheelbase	211.5 cm		
Ground Clearance	33 cm		
Estimated Dry Weight	710 kg		
Cage	ROPS-approved profiled cage. Certified ISO 3471 and OSHA.		
Cargo Box Dimensions	96.5 x 138.4 x 30.5 cm		
Cargo Box Capacity	454 kg		
Tailgate Load Capacity	113.4 kg		
Storage Capacity*	Total: 62.3 L Under dash: 22.8 L Waterproof and removable box under passenger seat: 21 L Dash: 15 L Armrests and cup holders: 3.5 L		
Towing Capacity	1,134 kg		
Payload Capacity	680 kg		
Fuel Capacity	40 L		
Person Capacity	3		

FEATURES			
Gauge	7.6 in. (19.3 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trip and hour meters,	Lighting	140-W lighting output from four 35-W reflectors ensuring a wide visiblity and LED tail lights
fuel, gear position, ECO / ECO Off / Work modes, seat belt, diagnostics, clock, battery voltage, engine temperature		Winch	2,041 kg winch winch with roller fairlead
T-category features	Horn, flashers and position lamps, mirrors, hook on front metal bumper	Seat	60/40 VERSA-PRO bench seat with passengers bench flipping up, adjustable driver seat, underside hooks, reinforced seat skin and contoured bench to improve entrance/exit of the cab
Battery	12 V (30 amp/h)	Protection	Integrated front steel bumper, full skid plate
Magneto	650W	Hitch Type	2-in. hitch receiver, 7-pin trailer connection (12V)
Instrumentation	Two lighter type DC outlets, one in the console (20-A) and one in the under dash storage (20-A)	Steering Wheel	Adjustable tilt steering

Factory 2 years

