

HIGHLIGHTS

- Rotax® V-Twin engine
- Arched double A-arm front suspension with front sway bar
 Front and rear FOX† 1.5 PODIUM† RC2 shocks
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- 12-in. cast-aluminum beadlock wheels
- 25-in. ITP Holeshot ATR tires
- · Front & central skid plate
- Aluminum taper-profile handlebar with full wrap handguards
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Torsional Trailing arm Independent (TTI) rear suspension
- Anti-Lock Braking System (ABS)
- Multifunction digital gauge
- X-package coloration, graphics and seat cover



ENGINE	650		
Туре	59HP, Rotax 649.6 cc V-twin, liquid cooled		
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)		
Transmission	CVT, P / R / N / H / L, standard engine braking		
Drive Train	Selectable 2WD / 4WD with Brake Traction Control (BTC)		
Power Steering	Tri-Mode Dynamic Power Steering (DPS)		
Speed Category	More than 60 km/h		
SUSPENSIONS			
Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3cm) travel		
Front Shocks	FOX† 1.5 PODIUM† RC2		
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25,1 cm) travel		
Rear Shocks	FOX† 1.5 PODIUM† RC2		
TIRES / WHEELS			
Front Tires	ITP Holeshot† ATR 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)		
Rear Tires	ITP Holeshot† ATR 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)		
Wheels	12-in. cast-aluminum beadlock		
BRAKES			
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers		
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper		

DIMENSIONS / CAPACITIES

·			
Estimated Dry Weight *	668 lb (303 kg)		
LxWxH	86 x 48 x 49 in. (218.4 x 121.9 x 124 cm)		
Wheelbase	51 in. (129.5 cm)		
Ground Clearance	10.5 in. (26.7 cm)		
Seat Height	34.5 in. (87.7 cm)		
Rack Capacity	Rear: 35 lb (16 kg)		
Storage Capacity	N/A		
Towing Capacity	660 Kg trailer with brakes and 335 kg trailer without brakes		
Fuel Capacity	5.4 gal (20.5 L)		

EE	Δ٦	П	ID	

FEATURES		
Gauge	4.5-in. digital display: Speedometer, tachometer, odometer, trip & hour meters,gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge & clock	
Instrumentation	Lighter type DC Outlet in console, standard connector in the back (15-A)	
Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)	
Lighting	240 W from 4 fender mounted projector beam headlamps (60-W) with tail light / brake light	
Winch	N/A	
T-Category features	Towing hitch with trailer plug, directionnal indicators, position lamps, mirrors, horn	
Seat	Standard	
Protection	"Front bumper Aluminum taper-profile handlebar with full wrap handguards Front & central skid plate"	

WARRANTY 2-years BRP limited warranty Factory warranty

