

MY23 MAVERICK X RC TURBO RR



■ Mineral Gray & Desert Tan

HIGHLIGHTS

- Smart-Lok™* front differential
- FOX† 3.0 PODIUM RC2† shocks with bypass
- Belt monitoring system
- 850 W Magneto
- 7.6 in. (19.3 cm) digital display with keypad
- X-package graphics/seats
- 4-point harness with shoulder pads
- Can-Am LED signature
- 15 in. (38.1 cm) cast-aluminum beadlock wheels
- 32 in. (81.3 cm) Maxxis Liberty tires
- Front bumper, half-doors, aluminum roof, intrusion bar
- Front tow hook
- 4,500-lb (2,041 kg) winch with synthetic rope
- HMWPE differential and under bumper skid plates
- UHMWPE front and rear suspension arm
- UHMWPE rock sliders
- Horn, Buzzer & Evap system

ENGINE

Type	149 kW (200 hp*), Rotax® ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P
Drive Train	Lockable front differential with exclusive Smart-Lok* technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD ROCK / 4WD TRAIL <i>*Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry</i>
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)

SUSPENSIONS

Front Suspension	Arched double A-arm with sway bar / 22 in. (55.9 cm) travel / Trophy truck inspired arms
Front Shocks	FOX† 2.5 PODIUM RC2† Piggyback with bypass, dual speed compression and rebound adjustments
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links / 24 in. (61 cm) travel
Rear Shocks	FOX† 3.0 PODIUM RC2† remote reservoir with bypass, dual speed compression and rebound adjustments

TIRES / WHEELS

Front Tires / Rear Tires	Maxxis Liberty† 32 x 10 / 10 x 15 in. (81.3 x 25.4 / 25.4 x 38.1 cm)
Wheels	15 in. (38.1 cm) cast-aluminum beadlock

BRAKES

Front	Dual 262 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm disc brakes with hydraulic twin-piston calipers

DIMENSIONS / CAPACITIES

Estimated Dry Weight *	1,843 lb (836 kg)
Chassis / Cage	Dual-phase 980 steel
L x W x H	134.5 x 72.8 x 68.5 in. (341.6 x 184.9 x 174 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L)
Fuel Capacity	10.5 gal (40 L)

FEATURES

Gauge	7.6 in. (19.3 cm) wide digital display with keypad
Instrumentation	DC Outlet (10-A)
Magneto	850 W
Ignition	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Lighting	LED headlights LED signature LED tail lights
Winch	4,500 lb (2,041 kg) winch with synthetic rope
Protection	Front bumper Half-doors Aluminum roof Intrusion bar 4-point harness with shoulder pads UHMWPE rock sliders HMWPE skidplates: Full heavy duty with differential / Under bumper / Front and rear suspension arm Rear tow hook

WARRANTY

Factory warranty	2-year BRP limited warranty
------------------	-----------------------------

*149kw/200hp based on MY22 U.S. EPA certification, or 145kw/195hp based on current EU NRRM certification.



©2022 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †All trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

